

ModulDOS Produkt 2

Activator for use in perc and hydrocarbon solvents; aqueous

- PROPERTIES:**
- supports the cleaning operation
 - improves the removal of wet-bound soil and pigments
 - ideal for supporting the cleaning process with polyester and cotton workwear

APPLICATION: ModulDOS Produkt 2 is used to support the cleaning process in the ModulDOS-System.

Dosing in accordance with BÜFA ModulDOS-System: The dosing in the BÜFA ModulDOS-System is 3 - 8 ml/kg load (0.46 - 1.23 fl oz/ 10 lbs) in the 1-bath method resp. 8 - 20 ml/kg load (1.23 - 3.07 fl oz/10 lbs) – depending on the sensitiveness of the textiles to water – into the 1st bath of a 2-bath method.

Hint: Because ModulDOS Produkt 2 contains water the recommended dosages depend on the sensitiveness of the textile to water.

TECHNICAL DATA:	Density 20 °C (68 °F)	1.0 g/ml
	pH-value	7.5 - 8.0

HINTS: Storage
Store in a frost-proof environment, even though frozen product can be used again after thawing without any loss of quality. Keep package closed tightly. The product can be stored for at least 24 months in its original sealed packing.

1109

For industrial use only. This information sheet is for guidance only. The data set out here are based on the current status of our knowledge and experience. They do not in any way absolve users of the need to carry out their own checks and tests for suitability of the products for the intended processes and purposes. The data in this information sheet do not represent assurance of properties and stability of the products we are to supply. Subject to technical modifications within reason. The current version of the EU Material Safety Data Sheet must also be observed.